

Specifications


- Input Voltage Range (for online operation):**
84-140 VAC
- Operating Frequency (online):**
50/60 Hz \pm 5 Hz
- Output Voltage Waveform:**
Stepped sine wave
- UPS and Surge Protection (both models):**
Three battery backed UPS outlets and one surge protection only outlet
- Safety Certification:**
UL1778, C-UL Listed
- Data Line Protection:**
RJ-45 port for surge protection
- Indicators:**
LED alarm
- Alarms:**
Audible, LED
- Dimensions:**
PSA: 3.7 x 14 x 6.7 in
PSP: 3.4 x 8.5 x 9.9 in
- Warranty:**
Two-year limited replacement warranty



Standard Features

- Full sequenced battery testing to ensure batteries are available when needed
- Advanced early warning of UPS shutdown
- Automatic Voltage Regulation (AVR) Technology (PSA)
- User replaceable batteries

Approvals



Part Number/Price

Part #	Model #	Capacity (Va/Watts)	Volts, Frequency In/Out	Full Load	Weight	Input Plug/ Output Receptacle	Price
153594	PSP	500/300	115V 50/60Hz	5 minutes	8.8/4.0 kg	NEMA Type 5 - 15R (3)	Consult
153595	PSA	500/300	115V 50/60Hz	5 minutes	15.9/7.2 kg	NEMA Type 5 - 15R (3)	Consult

Specifications

- Input Voltage Range (for online operation):**
89-151 VAC (3S)
93-138 VAC (5S)
- Operating Frequency (online):**
50/60 Hz out sensing
- UPS and Surge Protection:**
Both models
- Safety Markings:**
UL, CUL, NOM
- Data Line Protection:**
Yes, RJ45
- Indicators:**
Power, LED
- Alarms:**
No
- Dimensions:**
Model 3S: (H x W x D) 3.4 x 5.5 x 13.2 in
Model 5S: (H x W x D) 9.8 x 3.4 x 10.2 in
- Warranty:**
Three-year limited warranty



Standard Features

- Five outlets with surge protection (both)
- Five outlets with battery back up and surge protection
- Coax surge protection (5S)
- Replaceable battery

Part Number/Price

Part #	Model #	Capacity (Va/Watts)	Volts, Frequency In/Out	Weight	Input Plug/Output Receptacle	Price
154127	Eaton 3S	550/330	120 V	10 lb	NEMA Type 5-15R	Consult
154128	Eaton 5S	700/450	120 V	16 lb	NEMA Type 5-15R	Consult