



**Standard Features**

- Capacities between 300g and 6,000g
- Internal resolution: 1/600,000
- LCD display
- Quick response
- Accumulation, Counting and Percentage modes
- 13 different units of measure
- Detachable enclosed weighing chamber (in capacities ≤1 kg)
- Battery operation for up to 40 hours of continuous use (without backlight)
- Standard RS-232 interface for connecting to printer or PC
- Plastic enclosure
- AC adapter

APPROVALS



**Specifications**

	EQ-300 <sup>^</sup>	EQ-600 <sup>^</sup>	EQ-1500	EQ-3000	EQ-6000
Part #	165338	165339	165340	165341	132435
List Price	Consult	Consult	Consult	Consult	Consult
Capacity	300g	600g	1,500g	3,000g	6,000g
Resolution	0.01g	0.02g	0.05g	0.1g	0.2g
Weighing Units	Gram, Carat, Ounce, Ounce Troy, Pound, Pennyweight, Grain, Momme, Hong Kong Tael, Singapore Tael, Taiwan Tael, Tola				
Operating Modes	Weighing, Percent Weighing, Parts Counting, Accumulation				
Repeatability (+/-)	0.01g	0.02g	0.05g	0.1g	0.2g
Linearity (+/-)	0.02g	0.04g	0.1g	0.2g	0.4g
Stabilization Time	2 seconds				
Operating Temperature	32° F to 104° F (0° C to 40° C)				
Weighing Chamber	6.7 x 5.7 x 3.1 in (170 x 145 x 80 mm)		N/A	N/A	N/A
Pan Size	Ø 4.7 in (Ø 120 mm)		4.8 in x 5.6 in (122 mm x 142 mm)		
Dimensions	7.1 x 8.7 x 3.3 in (180 x 220 x 85 mm)				
Est. Ship Weight	6.6 lb (3 kg)				
Calibration Weight	300g	600g	1,500g	3,000g	6,000g
Power	AC adapter (12V/500 mA); internal rechargeable battery (6V/1.2Ah)				
Warranty	One-year Limited Warranty				
Return Policy	Rice Lake Standard Policy				

<sup>^</sup>Weighing Chamber

## Part Number/Price

Part #	Model #	Capacity	Est. Weight	Price
165338	EQ-300	300 g x 0.01 g	6 lb	Consult
165339	EQ-600	600 g x 0.02 g	6 lb	Consult
165340	EQ-1500	1,500 g x 0.05 g	6 lb	Consult
165341	EQ-3000	3,000 g x 0.1 g	6 lb	Consult
132435	EQ-6000	6,000 g x 0.2 g	6 lb	Consult

## Options/Accessories

Part #	Description	Price
41279	Printer cable, DB9M to 25-Pin M	Consult
103141	SP712 dot matrix printer, tear bar	Consult
119919	AbleCable RS-232/USB cable (requires 130789)	Consult
130789	Slim line null modem adapter	Consult
131135	Aluminum case	Consult
165183	AC adapter, 110-240 VAC, interchangeable plugs	Consult



PN 165183 Multi-range AC adapter and multi-plug