

# Honeywell DMXREW1

Label Rewinder/Unwinder



## Standard Features

- Rewinds or dispenses label rolls up to 4 in (101.6 mm) wide, up to 8 in (203 mm) in diameter at 10 in (254 mm) per second
- Adjustable core holder
- Coreless rewinding
- Steel construction
- Anti-slip feet
- Constant adjustable Torque™ technology
- Bidirectional operation
- ON-OFF start/stop switch
- Inner label flange to keep edge of label web aligned as labels are rewound
- Compatible with all Honeywell I Series and Rice Lake SURVIVOR® SST printers

## APPROVALS



## Specifications

### Label Width:

Up to 4.5 in (113 mm)

### Maximum Label Roll Weight:

8.5 lb (3.9 kg)

### Label Roll Diameter:

Up to 8 in (200 mm)

### Core Diameter:

Use any cardboard core from 1 in to 4 in (25 mm to 102 mm)

### Speed:

Up to 10 ips (250+ mm/sec)  
Switch adjustable rewind force  
No adjustments are required

### Start/Stop:

Convenient ON-OFF switch

### Direction:

Bidirectional

### Power Requirements:

115 VAC 60 Hz

### Overall Size:

(H x W x D): 9 x 6 x 11 in (229 x 152 x 279 mm)

### Weight:

13 lb (5.9 kg)

### Approvals:

UL listed, CSA certified

### Warranty:

One-year limited warranty on parts and labor

## Part Number/Price

Part #	Description	Est. Weight	Price
68517	Honeywell REW1 label rewinder/unwinder, 115 VAC	14 lb	Consult