

## Specifications

- Capacity:**  
5,000 lb
- Inside Dimension:**  
(L x W) 8 ft x 2 ft 10 in
- Outside Dimension:**  
(L x W x H) 9 ft 1 in x 3 ft 11 in x 8 ft 2 in
- Warranty:**  
Two-year limited warranty
- Approvals:**  
NTEP CC 99-091  
Measurement Canada AM-5284



SAS shown with head gate and optional enclosure

## Standard Features

- Swing gates, sliding gates, combination swing and slide gate, or head gate with swing or slide gate
- 48 in solid kick panel sides
- Ships assembled
- Durable X-Lug or X-Plank floor over steel
- Rugged all-weather powder paint

## APPROVALS



Measurement  
Canada  
Approved

## Part Number/Price

Part #	Inside Dimensions (L x W)	Outside Dimensions (L x W x H)	Description	Est. Weight	Price
171255	8 ft x 2 ft 10 in	9 ft 1 in x 3 ft 11 in x 8 ft 2 in	SAS, one slide gate and one swing gate, X-Lug	2,300 lb	Consult
172378	8 ft x 2 ft 10 in	9 ft 1 in x 3 ft 11 in x 8 ft 2 in	SAS, two swing gates, X-Lug	2,300 lb	Consult
172379	8 ft x 2 ft 10 in	9 ft 1 in x 3 ft 11 in x 8 ft 2 in	SAS, two slide gates, X-Lug	2,300 lb	Consult
176320	8 ft x 2 ft 10 in	9 ft 1 in x 3 ft 11 in x 8 ft 2 in	SAS, one head gate and one swing gate, X-Lug	2,270 lb	Consult
176550	8 ft x 2 ft 10 in	9 ft 1 in x 3 ft 11 in x 8 ft 2 in	SAS, one head gate and one slide gate, X-Lug	2,360 lb	Consult

Price does not include instrumentation

## Options/Accessories

Part #	Description	Price
168774	Enclosure, light duty	Consult
172852	RS420 portable stick reader, Allflex with IEC cable, data cable and external power adapter recharger	Consult
173118	Bluetooth® kit for RS420 stick reader	Consult
172854	920i Single Animal Rate of Gain	Consult
173139	920i Single Animal Rate of Gain weighcenter	Consult
177788	Transient protection package	Consult
23113	TM-U295 printer	Consult
15547	Blunt end cable for printer to indicator	Consult
131670	14 ft 4-pin male connector to blunt end cable	Consult
153765	Battery box without air compressor	Consult
189536	Solar panel retrofit kit	Consult