OHAUS



Capacity: 200 g-5,000 g Readability: 0.1 g-1 g

Standard Features

- Superior RF protection
- · Reliable, stable results
- CE listed and FCC Class B Part 15 operation
- Large, removable stainless steel weighing platform
- Low-profile design
- Standard AC adapter
- Easy operation
- · Low-battery indicator
- · Auto shut-off feature
- Overload protection
- Push-button calibration



Specifications

	CS200	CS2000	CS5000	CS2000P*	CS5000P*	CS200P*	
Part#	53493	53494	53495	53496	53497	83225	
List Price	Consult	Consult	Consult	Consult	Consult	Consult	
Capacity	200 g	2,000 g	5,000 g	2,000 g	5,000 g	200 g	
Resolution	0.1 g	1g	1 g	1g	1 g	0.1 g	
Weighing Modes	Grams, Pound/Ounce and Newton			4lb:6.55 oz x 0.05 oz	11 lb:0.4 oz x 0.1 oz	0 lb:7 oz x 0.01 oz	
Repeatability	0.1 g	1 g	1 g	1 g	1 g	0.1 g	
Linearity	±0.1 g	±1 g	±1 g	±1 g	±1 g	±0.1 g	
Stabilization Time	3 seconds						
Operating Temperature	64°F to 77°F (18°C to 25°C)						
Pan Size	5.75 x 5.25 in (14.5 x 13.3 cm)						
Dimensions	(W x D x H) 8.0 x 5.5 x 1.5 in (20.3 x 14.0 x 3.8 cm)						
Weight (Approx.)	0.91 lb (0.47 kg)						
Power	3 AA alkaline batteries (included) or AC adapter (included)						
Battery Life	300 hours						
Warranty	One-year Limited Warranty						
Return Policy	OHAUS Standard Policy - restock fee may apply						
*Includes IIC postal short							

^{*}Includes US postal chart

Part Number/Price

Part#	Model#	Description	Price
53493	CS200	200 g x 0.1 g	Consult
53494	CS2000	2,000 g x 1 g	Consult
53495	CS5000	5,000 g x 1 g	Consult
53496	CS2000P*	2,000 g x 1 g	Consult
53497	CS5000P*	5,000 g x 1 g	Consult
83225	CS200P*	200 g x 0.1 g	Consult

Options/Accessories

Part#	Model#	Description	Price
156234	90524-66	110/240 VAC AC power supply (requires PN 156235)	Consult
70434	80850075	Bowl, 1,050 mL	Consult
70435	80850076	Stainless steel weighing pan cover	Consult
156235	-	Plug set	Consult

