



Standard Features

- Touchless IR (infrared) sensors minimize keypad use
- Program IR sensor to control operations including print, tare and other selectable functions
- Color VGA, 5.7 in display with icons for simple menu navigation
- Multiple application modes designed for versatility
- AutoCal™ Calibration
- Robust IP 54 die-cast metal bottom housing with stainless steel pan
- Integral weigh below hook
- ENERGY STAR qualified adapter

APPROVALS

Measurement
 Canada
 Approved

Specifications

	Ex12001	Ex24001	Ex35001
Part#	157235	157236	157237
List Price	Consult	Consult	Consult
Capacity	12,000 g	24,000 g	35,000 g
Resolution	0.1 g		
Weighing Modes	Gram, Kilogram, Carat, Ounce, Troy Ounce, Pound., Pennyweight, Mommies, Grain, Tical, Tola, Newton, Mesghal, 3 Custom Units		
Operating Modes	Weighing, Counting, Animal/Dynamic Weighing, Checkweighing, Percent Weighing, Filling, Parts Counting, Totalization, Formulation, Differential Weighing, Density Determination, Peak Hold, Ingredient Costing, SQC		
Repeatability	±0.1 g		
Linearity	±0.2 g		
Stabilization Time	≤1 seconds		
Operating Temperature	14° F to 140° F (-10° C to 60° C)		
Pan Size	14.84 x 12.24 in (377 x 311 mm)		
Display Housing Dimensions	(W x D x H) 7.7 x 3.5 x 6.0 in (195 x 90 x 154 mm)		
Dimensions Base	(W x D x H) 14.84 x 4.72 x 17.44 in (377 x 120 x 443 mm)		
Weight (Approx.)	25 lb (12.5 kg)		
Calibration	Auto Cal internal calibration		
Power	AC adapter input: 100-240VAC 0.6A 50-60 Hz		
Warranty	Two-year Limited Warranty		
Return Policy	OHAUS Standard Policy - restock fee may apply		
Approvals	Measurement Canada AM-5957		

Part Number/Price

Part #	Model #	Description	Price
157235	EX12001	12,000 g x 0.1 g	Consult
157236	EX24001	24,000 g x 0.1 g	Consult
157237	EX35001	35,000 g x 0.1 g	Consult

Options/Accessories

Part #	Model #	Description	Price
157238	30078082	Tower mount display	Consult
77712	80500524	RS-232 cable, PC 25-pin to EX	Consult
70406	80500525	RS-232 cable, PC nine-pin to EX	Consult
156234	46001724	Multi-range AC adapter	Consult
156235	46001780	International plug set	Consult

