

Standard Features

- Designed for food service and other industrial applications with a focus on speed, durability and cleanliness
- All stainless steel, high-quality formed construction for sanitary cleaning and durability
- Checkweighing function for food packaging and preparation
- Internal rechargeable battery assures excellent portability
- Stainless steel housing and pan with non-slip rubber feet
- Checkweighing mode with 3-LED indicator and audible alarm
- Bright backlit LCD display
- Stable weight display within 2 seconds
- Multiple Weighing Units: lb, decimal/fractional oz, kg, g and lb
- AC power or internal rechargeable lead acid battery
- NSF-certified, USDA-AMS accepted, supports HACCP compliance
- EC/OIML type approved



APPROVALS



Measurement
Canada
Approved

Note: NTEP Certified and Measurement Canada 3000e approved resolution is specific only to model without the "H" suffix. Units ship in non-NTEP Certified resolution.

Specifications

	FD3H	FD3	FD6H	FD6	FD15H	FD15
Part#	102774	-	102775	-	102776	-
List Price	Consult	-	Consult	-	Consult	-
NTEP Part#	-	87824	-	87825	-	87826
NTEP List Price	-	Consult	-	Consult	-	Consult
Approvals	NSF listed/Certified to NSF C-2, UL C-US listed, NTEP CC 05-072 Class III, Measurement Canada AM-5582					
Capacity	6 lb	6 lb	15 lb	15 lb	30 lb	30 lb
Resolution	0.0002 lb	0.002 lb	0.001 lb	0.005 lb	0.001 lb	0.01 lb
Overload capacity	150%					
Operating Modes	Weighing, Checkweighing					
Repeatability	0.2 g		0.4 g		2 g	
Linearity	±0.2 g		±0.4 g		±0.2 g	
Stabilization Time	< 2 seconds					
Operating Temperature	14°F to 104°F (-10°C to 40°C) 10% to 85% relative humidity, non-condensing					
Environmental	IP43					
Pan Size	8.2 x 8.2 in (209 x 209 mm)					
Dimensions	(W x D x H) 9 x 12 x 2.8 in (300 x 223 x 71 mm)					
Weight (Approx.)	8 lb (3.6 kg)					
Est. Ship Weight	11 lb (5 kg)					
Power	120V AC adapter, 9V DC 0.5A 50/60Hz (Other adapters available by special request)					
Battery life	Maximum 120 hours					
Warranty	One-year Limited Warranty					
Return Policy	OHAUS Standard Policy - restock fee may apply					
UNIT OF MEASURE Kilogram	3 x 0.0001 kg	3 x 0.001 kg	6 x 0.0002kg	6 x 0.002 kg	15 x 0.005 kg	15 x 0.005 kg
Grams	3,000 x .1 g	3,000 x 1 g	6,000 x 0.2 g	6,000 x 2 g	-	15,000 x 5 g
Ounce	96 oz x 0.005 oz; 96 oz x 1/4 oz	96 oz x 0.05 oz or 1/4 oz	240 oz x 0.01 oz; 240 oz x 1/4 oz	240 oz x 0.1 oz or 1/4 oz	480 oz x 0.02 oz or 1/4 oz	480 oz x 0.2 oz or 1/4 oz
Pound x Ounce	6 lb 0 oz x 1/4 oz; 6 lb 0 oz x 0.1 oz	-	15 lb 0 oz x 0.1 oz; 15 lb 0 oz x 1/4 oz	-	30 lb 0 oz x 0.1 oz or 1/4 oz	-

Part Number/Price

Part #	Model #	Description	Price
102774	FD3H	6 lb x 0.0002 lb	Consult
87824	FD3 (NTEP)	6 lb x 0.002 lb	Consult
102775	FD6H	15 lb x 0.001 lb	Consult
87825	FD6 (NTEP)	15 lb x 0.005 lb	Consult
102776	FD15H	30 lb x 0.001 lb	Consult
87826	FD15 (NTEP)	30 lb x 0.01 lb	Consult

Options/Accessories

Part #	Model #	Description	Price
103118	80251394	Hard shell carrying case for FD	Consult
103116	80251141	Flat pan for FD or Valor 5000	Consult
103117	80251140	In-use cover for FD or Valor 5000	Consult
33451	3369-10	Polypropylene Maxi-Scoop™ 10 dia x 2.5 in deep (25.4 dia x 6.4 cm deep) with pouring spout, weight 145 g	Consult
97250	80250400	Stainless steel scoop 11.9 x 7.4 x 1.7 in (30 x 18.7 x 4.3 cm)	Consult
100292	80250954	Stainless steel scoop 17.2 x 11 x 3.4 in (44 x 28 x 8.5 cm)	Consult
98020	80500435	AC Adapter	Consult