

## Specifications

### Capacity:

- IGX 150 lb/60 kg x .05 lb/0.02 kg
- IGX 300 lb/150 kg x .1 lb/0.05 kg
- IGB 150 lb/60 kg x 0.05 lb/0.02 kg
- IGB 300 lb/150 kg x 0.1 lb/0.05 kg

### Accuracy:

- Configurable 1/3,000\*\*, 1/6,000, 1/7,500
- \*\*Legal for Trade setting

### Display:

- IGX: vacuum fluorescent display (VFD), 25 mm
- IGB: liquid crystal display (LCD), 29 mm

### Display Items:

- Weight: five-digits, center of zero, tare, checkweighing: over "H," under "L"

### Electrical Power:

- IGX: 120 V
- IGB: D size batteries or optional AC adapter (batteries not included) 500 hour battery life

### Operating Temperature:

- 23°F to 109°F (-5°C to 40°C)

### Warranty:

- One-year limited warranty

### Approvals:

- NTEP CC 05-020, Class III, 3,000 d



## Standard Features

- Ability to toggle between lb and kg
- Stainless steel cover with die-cast base
- Checkweighing function
- Configurable display resolution: 1/3,000, 1/6,000, 1/7,500 (NOTE: Legal for Trade setting is 1/3,000)
- 10 PLUs for storing tare, upper limit, lower limit

### IGX:

- Display, VFD
- Power, 120 VAC
- Internal buzzer

### IGB:

- Display, LCD
- Power, two D-size batteries or optional AC adapter
- Selectable automatic power-off function
- Batteries not included

## APPROVALS



## Part Number/Price

Part #	Capacity	Platform Dimensions	Est. Weight	Price
<b>IGX</b>				
84989	150 lb (60 kg) x 05 lb (0.02 kg)	15.75 x 21.65 x 5.43 in	43 lb	Consult
84990	300 lb (150 kg) x 0.1 lb (0.05 kg)	15.75 x 21.65 x 5.43 in	43 lb	Consult
<b>IGB</b>				
84991	150 lb (60 kg) x 0.05 lb (0.02 kg)	15.75 x 21.65 x 5.43 in	41 lb	Consult
84992	300 lb (150 kg) x 0.1 lb (0.05 kg)	15.75 x 21.65 x 5.43 in	41 lb	Consult

## Options/Accessories

Part #	Description	Price
75473	AC adapter (IGB only)	Consult
86545	Additional operating manual (IGX/IGB)	Consult

## Drawing Dimensions

A	15.75 in (400 mm)	E	29.06 in (738 mm)
B	21.65 in (550 mm)	F	22.00 in (560 mm)
C	9.84 in (250 mm)	G	33.70 in (856 mm)
D	5.43 in (138 mm)		

