

OHAUS® Ranger™ Count 3000

Industrial Counting Scales



Specifications

Internal Resolution:

1/500,000

Display:

Seven-segment 1/30,000, six-digit

Power Source (included):

100-240 VAC, 50-60 Hz internal universal power supply

Battery:

Lead acid, 210 hours, 12 hours recharge

Number or Scale Channels:

Optional second channel

Memory Items:

(30) 12-digit part number, average piece weights, check counting or checkweighing parameters, tare weights, accumulated weights or counts

Operating Temperature:

14° F to 104° F (-10° C to 40° C)

Dimensions:

Overall (L x W x H): 12.2 x 12.9 x 4.6 in (311 x 327 x 117 mm)

Platter Size

11.8 x 8.9 in (300 x 225 mm)

Approvals:

NTEP Certified 13-022 3000 e
CAN/CSA-C22.2 No. 61010-1-04
UL Std. No. 61010-1 (2nd edition)

Warranty:

One-year limited warranty

Standard Features

- Weigh in kilograms, pounds, grams or ounces
- 30-item data storage
- Three backlit LCD display windows
- RS-232 output
- Quick stabilization

Approvals



Optional Features

- Ethernet
- Second platform

Part Number/Price

Part #	Model #	Description (lb (kg (oz (g)	Est. Weight	Price
157273	RC31P1502	3 x 0.0001 lb (1.5 x 0.00005 kg) (48 x 0.002 oz) (1,500 x 0.05 g)	12 lb (5.45 kg)	Consult
157275	RC31P3	6 x 0.0002 lb (3 x 0.0001 kg) (96 x 0.05 oz) (3,000 x 0.1 g)	12 lb (5.45 kg)	Consult
157277	RC31P6	15 x 0.0005 lb (6 x 0.0002 kg) (240 x 0.01 oz) (6,000 x 0.2 g)	12 lb (5.45 kg)	Consult
157278	RC31P15	30 x 0.001 lb (15 x 0.0005 kg) (480 x 0.02 oz) (15,000 x 0.5 g)	12 lb (5.45 kg)	Consult
157279	RC31P30	60 x 0.002 lb (30 x 0.001 kg) (960 x 0.05 oz) (30,000 x 1 g)	12 lb (5.45 kg)	Consult

Options/Accessories

Part #	Description	Price
157280	Remote second scale option kit	Consult
154638	Ethernet kit	Consult